

# TEMP°ALERT®

PROTECT PROPERTY FROM THE ADVERSE EFFECTS OF TEMPERATURE EXTREMES



## TA-40

### *Low Temperature Monitor*

- Activates any hardwire or wireless alarm system if temperature falls below +39°F (+4°C)
- Very small size for unobtrusive appearance
- Requires no power to operate
- Perfect for homes, vacation properties or any unattended building



**WINLAND**  
ELECTRONICS, INC.

# SPECIFICATIONS

## TA-40 TEMP°ALERT®

SPECIFICATION	VALUE
Contacts	Contact opening temperature $\leq 39.5^{\circ}\text{F} \pm 5.4^{\circ}\text{F}$ ( $4^{\circ}\text{C} \pm 3^{\circ}\text{C}$ )
Operating Temperature Range	+32 to +100° F (0 to +38° C)
Contact Ratings	Voltage $\leq$ to 24V AC/DC • Current $\leq$ 200 mA
Recommended Sensor Cable	18 to 24 gauge
Case Material	ABS plastic rated 94V-0
Dimensions	2.5" x .8" x .55" (6.4 cm x 2 cm x 1.4 cm)
Weight	3 oz. (85 g)
Color	Off-white
Mounting	2 screw holes (.165" dia.)
Master Pack Weight	Carton of 12: 1 pound (.45 kg)
Warranty	1 year limited



1950 Excel Drive  
Mankato, MN 56001  
1-800-635-4269  
In MN: 507-625-7231  
FAX: 507-387-2488  
[www.winlandsecurity.com](http://www.winlandsecurity.com)

